



## ANGLO - EGYPTIAN PAINTS

Port Said Street,  
El Shatby, ALEXANDRIA  
EGYPT  
Borg El Arab - 2<sup>nd</sup> Industrial Zone

### TECHNICAL DATA SPECIFICATION

#### ANGLOKYD LSP-6070 -W

#### DESCRIPTION

ANGLOKYD LSP-6070-W is a low viscosity long oil alkyd, for use in super gloss enamels. The properties of ANGLOKYD LSP-6070-W make it a very good binder when used alone or in combination with other resins, for superior quality non yellowing enamels for wood and steel, for architectural as well as industrial paints and primers.

#### APPLICATIONS

- Quality architectural enamels
- Structural steel maintenance coatings
- Wood coatings
- High gloss paints

#### COMPOSITION

Type of oil:	Soya
Type of Polyol:	Penta.
Oil length:	60%
Non volatile:	70% ± 1
Solvent:	White Spirit

#### FEATURES

- Easy brushing properties
- Good gloss and gloss retention
- Positive dry
- Good levelling
- Very good flexibility

#### TECHNICAL CHARACTERISTICS

Viscosity Gardner:	Z4	(70% in W.S.)
Colour (Gardner):	Max. 5	
Acid Value:	Max. 8	

#### STORAGE

Resin should be stored indoors in the original containers in a dry place at 5-30° C

#### STABILITY

Provided above storage conditions are met, stability shall be maintained for 12 month.